

Herdict Query API

- Herdict Query API 1
- 1. Background 2
- 2. Transaction Q01 – Get reports 2
- 3. Download all reports 3
- 4. Version History 3

1. Background

This API allows clients to request report data from Herdict

2. Transaction Q01 – Get reports

Request:

<http://www.herdict.org/api/query/{version}>

If the *version* element is omitted, the latest version of the API will be used. The current version is “1”.

The request accepts the following querystring parameters:

Parameter	Description	Example(s)	Default
fsd	Date range boundary (earliest date, inclusive) in ISO 8601 format. Time zone is EST	2011-03-31	2009-01-01
fed	Date range boundary (latest date, inclusive) in ISO 8601 format. Time zone is EST	2011-06-15	Current date
fc	Country (two-letter ISO code)	AF	All countries
fs	Site (host name)	www.yahoo.com	All sites
ft	Report type	inaccessible accessible	All reports
page	Which page of results to return (first page is 1). No more than 5000 results will be returned per page	2	1

Examples:

<http://www.herdict.org/api/query>

<http://www.herdict.org/api/query?fs=www.google.com&page=2>

<http://www.herdict.org/api/query?fc=US&fsd=2011-01-01&fed=2011-02-28>

Response:

JSON formatted array of reports

Example:

```
[ {  
  "reportDate": " 2011-10-21T16:00:28 -0500",
```

